

3XR 3 Stainless steel body drilling pump**Application**

- Pumping for drilling, well, tank
- For domestic (watering, irrigation) or industrial applications

Pompe

- Maximum liquid temperature: +35°C
- Maximum sand content: 0,25%
- Maximum immersion depth: 80 m
- Minimum borehole diameter: 3"
- Curved tolerance in accordance with the standard ISO 9906

Moteur


- Rewindable motor

Identification codes

3	XR	m	3	/11	-0.37	
						Nominal power (kW)
						Number of impeller stages
						Nominal flow (m³/h)
						Single phase
						Submersible borehole pump
						Minimum borehole diameter (in ")

Technical data

MODEL	kW	Q (m³/h)	0	0.3	0.6	0.9	1.2	1.5	1.8	2.1	2.4	2.7	3	3.3	3.6
		Q (l/min)	0	5	10	15	20	25	30	35	40	45	50	55	60
3XRm3/8-0.25	0.25		32	32	32	31	30	29	28	27	26	23	20	16	12
3XRm3/11-0.37	0.37		44	44	43	43	41	40	39	37	35	31	27	22	16
3XR3/11-0.37	0.37		44	44	43	43	41	40	39	37	35	31	27	22	16
3XRm3/16-0.55	0.55		64	64	63	62	60	59	56	54	51	45	39	32	23
3XR3/16-0.55	0.55		64	64	63	62	60	59	56	54	51	45	39	32	23
3XRm3/21-0.75	0.75		85	84	83	81	79	77	74	70	67	60	52	43	31
3XR3/21-0.75	0.75		85	84	83	81	79	77	74	70	67	60	52	43	31
3XR3/31-1.1	1.1		125	124	122	120	116	114	109	104	99	88	76	63	45
3XRm3/31-1.1	1.1		125	124	122	120	116	114	109	104	99	88	76	63	45
3XRm3/37-1.5	1.5		149	148	146	143	139	136	130	124	118	105	91	75	54
Controlbox 3XRm3/11-0.37	0														
Controlbox 3XRm3/16-0.55	0														
Controlbox 3XRm3/21-0.75	0														
Controlbox 3XRm3/31-1.1	0														
Spare motor 3XRm3/16-0.55	0														
Spare motor 3XRm3/21-0.75	0														
Spare motor 3XRm3/31-1.1	0														
Spare motor 3XRm3/11-0.37	0														

Dimensions

MODEL	DN	P	M	T	poidsP	poidsM	poidsT
3XRm3/8-0.25	1	405	308	713	1.8	4.8	6.6
3XRm3/11-0.37	1	483	338	821	2.1	5.6	7.7
3XR3/11-0.37	1	483	308	821	2.1	5.6	7.7
3XRm3/16-0.55	1	613	368	981	2.5	6.4	8.9
3XR3/16-0.55	1	613	338	951	2.5	5.6	8.9
3XRm3/21-0.75	1	768	408	1176	3.2	7.5	10.7
3XR3/21-0.75	1	768	368	1136	3.2	7.5	10.7
3XR3/31-1.1	1	1029	493	1522	4.1	10	14.1
3XRm3/31-1.1	1	1029	493	1522	4.1	10	14.1
3XRm3/37-1.5	1	1209	543	1752	4.7	11.3	16
Controlbox 3XRm3/11-0.37							
Controlbox 3XRm3/16-0.55							
Controlbox 3XRm3/21-0.75							
Controlbox 3XRm3/31-1.1							
Spare motor 3XRm3/16-0.55							
Spare motor 3XRm3/21-0.75							
Spare motor 3XRm3/31-1.1							
Spare motor 3XRm3/11-0.37							