

## Features

Self - priming garden pump, also suitable for the pressurisation of water in domestic applications.

Compact, light, robust and easy to use.

Motor with thermal protector.



## Plastic Pump Housing

Model	XKJ-604P	XKJ-804P	XKJ-904P	XKJ-1104P	XKJ-1304P
Voltage	220V-240V	220V-240V	220V-240V	220V-240V	220V-240V
Frequency	50Hz	50Hz	50Hz	50Hz	50Hz
Rated Power	600W	800W	900W	1100W	1300W
Max. Head	35m	40m	43m	46m	48m
Max. Flow	3.0m <sup>3</sup> /h	3.6m <sup>3</sup> /h	3.6m <sup>3</sup> /h	4.6m <sup>3</sup> /h	5.0m <sup>3</sup> /h
Max. Suction Depth	7m	7m	8m	8m	8m
Outlet/Inlet	1"×1"	1"×1"	1"×1"	1"×1"	1"×1"
Power Cable Type	H07RN-F 1.5m	H07RN-F 1.5m	H07RN-F 1.5m	H07RN-F 1.5m	H07RN-F 1.5m
Electric Protection Class	IPX4	IPX4	IPX4	IPX4	IPX4
Max. Delivery Temperature	35 °C	35 °C	35 °C	35 °C	35 °C

## Features

Self - priming garden pump, also suitable for the pressurisation of water in domestic applications.

Compact, light, robust and easy to use.

Motor with thermal protector.



## Inox Pump Housing

Model	XKJ-604S	XKJ-804S	XKJ-904S	XKJ-1104S	XKJ-1304S
Voltage	220V-240V	220V-240V	220V-240V	220V-240V	220V-240V
Frequency	50Hz	50Hz	50Hz	50Hz	50Hz
Rated Power	600W	800W	900W	1100W	1300W
Max. Head	35m	40m	43m	46m	48m
Max. Flow	3.0m <sup>3</sup> /h	3.6m <sup>3</sup> /h	3.6m <sup>3</sup> /h	4.6m <sup>3</sup> /h	5.0m <sup>3</sup> /h
Max. Suction Depth	7m	7m	8m	8m	8m
Outlet/Inlet	1"×1"	1"×1"	1"×1"	1"×1"	1"×1"
Power Cable Type	H07RN-F 1.5m	H07RN-F 1.5m	H07RN-F 1.5m	H07RN-F 1.5m	H07RN-F 1.5m
Electric Protection Class	IPX4	IPX4	IPX4	IPX4	IPX4
Max. Delivery Temperature	35 °C	35 °C	35 °C	35 °C	35 °C

